

8W Dimmable Downlight



Features

- Finish: White, Black, Brushed Nickel, Brush Alum,
- Shiny Alum, Polished Nickel
- Instant start up
- 25° Angle of tilt (IP20)
- Low electromagnetic interference
- 50,000 hour lifetime



Applications

- Offices ➤ Schools ➤ Hospitals
- Public buildings

Technical Specification

➤ Beam Angle	40°
➤ Colour Rendering (RA)	80
➤ CCT	3000K, 4000K, 5000K
➤ Operating Temperature	-20°~50°
➤ IP Rating	IP20, IP65
➤ Certifications	CE & ROHS, 'ECA Compliant', LM-79, LM-80
➤ Driver:	External
➤ Energy Rating	A

Dimming functionality requires compatible dimmer







8W

➔ Model	ETW-DD-8W	ETW-DD-8W
➔ Luminaire Rated Power Consumption	8W	8W
➔ Lumens	490	490
➔ Luminous Efficiency lm/w	61	61
➔ Dimensions	79mm cut-out	69mm cut-out
➔ Voltage	240V	240V
➔ Material	Aluminium	Aluminium
➔ Comments	gimballed	fixed





sustainable growth

China Office

 20A, Tower 3, Tianshan Rd 600
Shanghai, 200051, China
 www.ecotecworld.com

Germany Office

 Kappenbergshof 8,
D-49843 Uelsen, Germany
 www.ecotecworld.com

HK office

 Room 1203, Euro Trade
Centre 13-14 Connaught
Road, HK
 www.ecotecworld.com

UK Office

 30 St Giles Oxford
OX13LE, UK
 www.ecotecworld.com